

SunTelligent Product Line

Solar Electric Power Systems



General Features

The CDM Wireless SunTelligent custom product line are self-contained Solar Packs for remote wireless surveillance applications. They are available in 12, 24, 36 or 48 Volts DC. Integrated AC converters are available for applications that include equipment that is powered by 24 to 120VAC.

With Each solar installation being slightly different due to specific power requirements, geographic location and battery backup, CDM's engineering staff custom designs solar packs for almost any application.

Manufactured for commercial applications using the best available materials on the market, the SunTelligent product lines are engineered for quick deployment and 24/7/365 operation with virtually no maintenance. Systems ship factory assembled, wired, tested and include all hardware, batteries, controllers, enclosures, etc. Poles are not included.

The CDM Wireless Solar Pack includes an "intelligent technology" power system that will disconnect the battery from equipment in the event the voltage drops below 11.6 volts. As the batteries recharge, the system brings the devices back online, significantly prolonging the life of the battery(s).

In addition to providing uninterrupted power, the SunTelligent Series can be equipped with an optional Status and Alert module. This module provides real time measurements of the voltage output of the solar panel(s) and battery bank as well as temperature data. The status can be in the form of a simple web based application or provide additional data and logging. Alerts can be sent via email or monitored by software.





Solar Electric Power Systems Model: SunTel 265-400

Hardware Specifications

Model SunTel 265-400

Pmax	265 Watt
Voc	38.3V
Isc	9.26A
Vmp	31.0V
Imp	8.55A
Dimensions	65.43"L 38.98"W 1.8"H
Weight	41.9 lbs.
WindLoad	125 mph

Battery(s)

Voltage	12vdc x 4
Amp Hours	400 Amps.
Construction	AGM Deep Cell Solar
Dimensions	20.75" L x 8.11" W x 8.43" H
Weight	114.6 lbs. ea.

Smart Technology MPPT Power Controller

Peak Efficiency	97.5%
Nom Battery Voltage	12-24 Vdc.
Max battery Current	15 A.
Battery Voltage Range	7 – 36 Volts
Max PV Open Circuit voltage	75 Vdc.
Nominal Max PV input	50 Vdc.
Output Rating	15 A
Self Consumption	22ma
Transient Surge Protection	4x1500 Watts
Operating Temp	-40c to +60c
Electronic Protections	Overload, short circuit, high voltage, reverse polarity, battery, PV & load, lightning & transient surges, high temp, Reversecurrent at night.

Weatherized battery box

Nema 3R Vented aluminum enclosure suitable for ground mount.
Dimensions 16"x48"x24"

Side of pole solar panel mounts

5052 H32 Aluminum for side of pole mount. Fortop of pole mounts cold roll steel and special high strength hot roll steel is used as well as tilt plates and cross rails to stay in compliance with the 125 mph wind load rating.